

DECKOVER – STANDARD DUTY



CAM
SUPERLINE

DECKOVER – STANDARD DUTY

STANDARD FEATURES

- Steel Plated Tongue
- Dexter EZ Lube Axles (Oil Bath on 8 Ton)
- Slipper Spring Suspension
- Electric Brakes (2) Axles
- 6' Adjustable Spring Assisted (Angle or Wood Filled) Ramps
- Stake Pockets and Rub Rail
- LED Lights – Rubber Mounted
- Tool Box
- Adjustable 2-5/16" Ball Coupler or Pintle
- 12K Bolt-on Drop Leg Jack
- D-Ring Tie Downs (6) – 5/8"
- Hemlock Deck (Oak on 8 & 10 Ton)
- Mud Flaps
- Solar Charged Breakaway
- Sealed Wiring Harness
- 7-Way RV Plug
- Safety Chains
- Epoxy Primer
- Polyurethane Paint Finish
- Colors (standard): Black, Yellow, Red, Gray, Orange & Blue
- Two Year Warranty



10 Ton Model (Tri-axle) 5' Lay Down Ramps (standard)



Underbody Tool Box (optional)

SPECIFICATIONS

Model#	5CAM818DO	6CAM818DO	7CAM818DO	8CAM818DO	10CAM823DO
GVWR:	11,960 lbs.	13,800 lbs.	16,100 lbs.	18,400 lbs.	23,000 lbs.
Empty Weight:	3,300 lbs.	3,400 lbs.	3,500 lbs.	3,950 lbs.	5,810 lbs.
Payload:	8,660 lbs.	10,400 lbs.	12,600 lbs.	14,450 lbs.	17,190 lbs.
Deck Length:	18' (14' Flat, 4' B/T)	18' (14' Flat, 4' B/T)	18' (14' Flat, 4' B/T)	18' (14' Flat, 4' B/T)	23' (18' Flat, 5' B/T)
Overall Width:	96"	96"	96"	96"	96"
Deck Height:	33"	34"	35"	35"	35"
Axle Capacity:	6,000 lbs.	6,000 lbs.	7,000 lbs.	8,000 lbs.	7,000 lbs. (Tri-Axle)
Radial Tire Size:	225/75R15LRD	235/80R16LRE	235/80R16LRE	215/75R17.5LRH	235/85R16LRG
Main Frame & Tongue:	8" I-Beam @ 10#	8" I-Beam @ 10#	8" I-Beam @ 10#	8" I-Beam @ 13#	10" I-Beam @ 15#
Crossmember:	3" Channel @4.1#	3" Channel @4.1#	3" Channel @4.1#	3" Channel @4.1#	3" Channel @4.1#

OPTIONS AVAILABLE

- Extra Deck Width (102")
- Extra Deck Length (32' Max)
- 5' Spring Assisted Split Landscape Ramp
- Spare Tire & Wheel
- Spare Tire Mount
- Oak Deck (Standard on 8 & 10 Ton)
- 3/16" Diamond Plate Decking
- Gooseneck with Adjustable Coupler and Dual 12K Jacks (30' Max)
- Self Cleaning Beavertail & Ramps
- 5' Pop Up Beavertail w/6' Slide in Ramps & Stabilizer Feet
- Self Leveling Ramps w/Flip-Out Leg
- Hydraulic Surge Brakes (Free Backing)
- Underbody Tool Box (14"x16"x36")
- Winch Mount
- Torflex Axles
- Forklift Tread Package
- Aluminum Wheels
- Additional D-Ring Tie Downs – 5/8"
- Undercoating
- 25K Ball Coupler
- Custom Colors



Gooseneck



Authorized Dealer

Printed in the USA

CAM
SUPERLINE

www.camsuperline.com

CAM Superline, Inc.

4763 Zane Miller Drive • Waynesboro, PA 17268

(800) 378-7623 • Fax (800) 279-7578