



SPECIFICATIONS PAGE

20 and 25 TON HEAVY DUTY DECKOVER TRAILER



20 and 25 TON HD DECKOVER STANDARD FEATURES

Steel Plated Tongue
Hi-Tensile Steel Construction
Full Pierced Beam Construction
Adjustable Pintle Hitch
Safety Chains (5/8" High Test)
Sealed 7-Pin Plug w/ Arctic Flex Whip
Zip Breakaway System
Dual 50K 2-Speed Jacks (Bolt-On)
Oil Bath Axles
Axle Springs: 3 Leaf (50,000 lb. Capacity)
Spring Park Brake On All Axles
Hutch H-9700 Suspension

Silver Wheels
Epoxy Primer
Polyurethane Paint Finish
Nominal 2" Oak Deck
Spare Tire Mount (Under Bed)
D-Ring Tie-Downs - 1" (12)
Toolbox
Mud Flaps
Steps (4)
Sealed Wiring Harness
LED Lights - Rubber Mounted
Three Year Warranty

Specifications subject to change without notice.





SPECIFICATIONS PAGE

20 and 25 TON HEAVY DUTY DECKOVER TRAILER

	20' + 5' (Air)	24' + 5' (Air)
Model #	P20CAM8205TA	P25CAM8245TA
GVWR (lb.)	51750	65000
GAWR (lb. / Axle)	22500	22500
Curb Weight	9095	11575
Payload	42655	53425
Main Frame	14" I-Beam @ 22 lb	
Crossmembers	5" Channel	
Side Rail	8" Channel @ 11.5 lb	
Tongue	14" I-Beam @ 22 lb	
Beavertail	5' Beavertail	
Coupler	Adjustable Pintle Ring	
Jack	Dual 50K Bolt-On Drop Leg 2-Speed Jacks	
Axles	Oil Bath Axles	
Suspension	Hutch H-9700 Suspension	
Tires	235/75R17.5 LRH Dual	
Wheels	17.5" Dual	
Decking	Nominal 2" Oak Deck	
Lights	LED Lights - Rubber Mounted	
Electric Plug	Sealed 7 Pin Plug w/Arctic Flex Whip	
Finish	PPG Industrial Polyurethane Paint	
Overall Length	376"	424"
Deck Height	35"	
Coupler Height	21.5" - 30.5"	
Ramps	5' Bi-Directional Spring Assisted Wood Filled Ramps	

Specifications subject to change without notice.

