



# DECKOVER TRAILERS

## STANDARD DUTY

		8.5 x 20, 15.4K	8.5 x 22, 15.4K	8.5 x 24, 15.4K	8.5 x 20, 17.6K	8.5 x 22, 17.6K	8.5 x 24, 17.6K
Model #	Bumper Pull	PSD010220-BP-154	PSD010222-BP-154	PSD010224-BP-154	PSD010220-BP-176	PSD010222-BP-176	PSD010224-BP-176
	Gooseneck	PSD010220-GN-154	PSD010222-GN-154	PSD010224-GN-154	PSD010220-GN-176	PSD010222-GN-176	PSD010224-GN-176
GVWR (lbs)		15400	15400	15400	17600	17600	17600
GAWR (lbs/axle)		7000	7000	7000	8000	8000	8000
Curb Weight	Bumper Pull	2685	3070	3457	2985	3370	3757
	Gooseneck	3490	3870	4257	3790	4170	4557
Payload	Bumper Pull	12715	12330	11943	14615	14230	13843
	Gooseneck	11910	11530	11143	13810	13430	13043
Main Frame		W10 x 12#/ft., I-Beam					
Side Rails		5" C-Channel					
Cross Members		3" C-Channel (16" On-Center)					
Coupler	Bumper Pull	Adjustable 2-5/16" Ball Coupler					
	Gooseneck	Adjustable 2-5/16" Gooseneck Coupler					
Jack	Bumper Pull	Setback HD 12K Drop Leg Jack					
	Gooseneck	Dual Setback HD 12K Drop Leg Jacks with Toolbox (Between Uprights), Tool Tray and Winch Receiver Tube (In Neck)					
Axles		Easy Lube Hubs with Brakes					
Suspension		Slipper Spring					
Tires		235/80R16 LRE					
Wheels		16", 8 on 6.5, Radial					
Decking		2 x 8 Pressure Treated Pine					
Lights		All LED Lights					
Electric Plug		7-Way RV-Style Molded Plug					
Finish		PPG Industrial Polyurethane Paint					
Overall Length	Bumper Pull	290"	314"	338"	290"	314"	338"
	Gooseneck	348"	372"	396"	348"	372"	396"
Deck Height		36"	36"	36"	36"	36"	36"
Coupler Height	Bumper Pull	Adjustable 21"-29"					
	Gooseneck	Adjustable 31" - 39-3/4"					
Ramps		8' Slide-In Fabricated Ramps					

Additional Configurations available. Contact your local dealer for more information.

## ADDITIONAL FEATURES

- HD Steel Bulkhead
- Safety Chains
- Zip Breakaway System
- Spare Tire Mount
- D-Ring Tie Downs (6)
- Stake Pockets and Rub Rail
- Sealed Wiring Harness
- Three Year Warranty



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.



# DECKOVER TRAILERS

## STANDARD DUTY BEAVERTAIL

		8.5 x 18 + 4, 15.4K	8.5 x 20 + 4, 15.4K	8.5 x 22 + 4, 15.4K	8.5 x 18 + 4, 17.6K	8.5 x 20 + 4, 17.6K	8.5 x 22 + 4, 17.6K
Model #	Bumper Pull	PSD0102184-BP-154	PSD0102204-BP-154	PSD0102224-BP-154	PSD0102184-BP-176	PSD0102204-BP-176	PSD0102224-BP-176
	Gooseneck	PSD0102184-GN-154	PSD0102204-GN-154	PSD0102224-GN-154	PSD0102184-GN-176	PSD0102204-GN-176	PSD0102224-GN-176
GVWR (lbs)		15400	15400	15400	17600	17600	17600
GAWR (lbs/axle)		7000	7000	7000	8000	8000	8000
Curb Weight	Bumper Pull	3130	3475	3825	3430	3775	4121
	Gooseneck	3930	4275	4625	4230	4575	4921
Payload	Bumper Pull	12270	11925	11575	14170	13825	13479
	Gooseneck	11470	11125	10775	13370	13025	12679
Main Frame		W10 x 12#/ft., I-Beam					
Side Rails		5" C-Channel					
Cross Members		3" C-Channel (16" On-Center)					
Coupler	Bumper Pull	Adjustable 2-5/16" Ball Coupler					
	Gooseneck	Adjustable 2-5/16" Gooseneck Coupler					
Jack	Bumper Pull	Setback HD 12K Drop Leg Jack					
	Gooseneck	Dual Setback HD 12K Drop Leg Jacks with Toolbox (Between Uprights), Tool Tray and Winch Receiver Tube (In Neck)					
Axles		Easy Lube Hubs with Brakes					
Suspension		Slipper Spring					
Tires		235/80R16 LRE					
Wheels		16", 8 on 6.5, Radial			17.5", 8 on 6.5		
Decking		2 x 8 Pressure Treated Pine					
Lights		All LED Lights					
Electric Plug		7-Way RV-Style Molded Plug					
Finish		PPG Industrial Polyurethane Paint					
Overall Length	Bumper Pull	323"	347"	371"	323"	347"	371"
	Gooseneck	371"	395"	419"	371"	395"	419"
Deck Height		36"	36"	36"	36"	36"	36"
Coupler Height	Bumper Pull	Adjustable 21" - 29"					
	Gooseneck	Adjustable 31" - 39.75"					
Ramps		5ft. 4" HD Channel Spring-Assist Standup Ramps with Adjustable Support Legs					

Additional Configurations available. Contact your local dealer for more information.

### ADDITIONAL FEATURES

- HD Steel Bulkhead
- Safety Chains
- Zip Breakaway System
- Spare Tire Mount
- D-Ring Tie Downs (6)
- Stake Pockets and Rub Rail
- Sealed Wiring Harness
- Three Year Warranty



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.