



SPECIFICATIONS PAGE

ADVANTAGE LOW PROFILE DUMP DUMP TRAILER



ADVANTAGE LOW PROFILE DUMP STANDARD FEATURES

- Adjustable 2-5/16" Ball Coupler or Pintle Ring
- Safety Chains
- 7-Way SAE Plug
- Zip Breakaway System
- Breakaway Switch
- Charge Wire with Circuit Breaker
- 7K Bolt-On Drop Leg Jack
- Double-Acting Tailgate with Chains
- Diamond Plate Fenders
- EZ Lube Axles
- Electric Brake Axles (2)

- Slipper Spring Suspension
- Silver Wheels
- Epoxy Primer
- Polyurethane Paint Finish
- Spare Tire Mount
- Sealed Wiring Harness
- LED Lights – Rubber Mounted
- Aluminum Lockable Pump Box
- Remote Control with 20' Cord
- 12V Deep-Cycle Battery
- Three Year Warranty

Specifications subject to change without notice.





SPECIFICATIONS PAGE

ADVANTAGE LOW PROFILE DUMP DUMP TRAILER

	60" x 10'	72.5" x 10'	72.5" x 10'	72.5" x 12'
Model #	P7510LPDT	P8610LPDT	P10610LPDT	P10612LPDT
GVWR (lb.)	7000	8050	9998	9998
GAWR (lb. / Axle)	3500	3500	5200	5200
Curb Weight	1780	1900	2080	2340
Payload	5220	6150	7918	7658
Frame	5" Channel	6" x 2" x 3/16" Rec. Tube		
Crossmembers	10 Gauge, Formed	3" Channel		
Tongue	5" Channel			
Coupler	Adjustable 2-5/16" Ball Coupler or Pintle Ring			
Jack	7K Bolt-On Drop Leg Jack			
Fenders	Diamond Plate			
Axles	3,500 lb, Greased		5,200 lb, Greased	
Suspension	Slipper Spring Suspension			
Tires	205/75R15 LRC		225/75R15 LRD	
Wheels	15"			
Volume Capacity	3.2 cu yd	3.9 cu yd		4.5 cu yd
Lights	LED Lights - Rubber Mounted			
Electric Plug	7-Way SAE Plug			
Finish	PPG Industrial Polyurethane Paint			
Overall Length	172"			196"
Bed Width Inside	60"	72.5"		
Bed Length Inside	120"			144"
Side Wall Height	20.5"			
Deck Height	26"	28"		
Coupler Height	14" - 22"			
Gate	Double-Acting Tailgate w/ Chains	Triple-Acting Tailgate w/Chains		
Hydraulic Cylinder	One 3.5" x 36"			
Hydraulic Pump	12V Single Acting			
Battery	12V Deep-Cycle Battery			
Dump Angle	48°			46°

Specifications subject to change without notice.

