

# ADVANTAGE LOW PROFILE HD DUMP DUMP TRAILER



## ADVANTAGE LOW PROFILE HD DUMP STANDARD FEATURES

- Tubular Main Frame
- 102" Width
- Adjustable 2-5/16" Ball Coupler or Pintle Ring
- Safety Chains
- 7-Way SAE Plug
- Zip Breakaway System
- Breakaway Switch
- Charge Wire with Circuit Breaker
- 7K Bolt-On Drop Leg Jack (12K on 146814LPDHT)
- Slide-Out Ladder Ramps (6')
- Triple-Acting Tailgate w/ Chains
- Diamond Plate Fenders
- EZ Lube Axles
- Electric Brake Axles (2)
- Nev-R-Adjust Brakes

- Slipper Spring Suspension
- Silver Wheels
- Epoxy Primer
- Polyurethane Paint Finish
- Spare Tire Mount
- D-Ring Tie-Downs - 1/2" (4)
- Storage Tray
- Sealed Wiring Harness
- LED Lights – Rubber Mounted
- Aluminum Lockable Pump Box
- Remote Control with 20' Cord
- 12V Deep-Cycle Battery
- HD Dual 3" Cylinders
- Three Year Warranty

*Specifications subject to change without notice.*



# SPECIFICATIONS PAGE

## ADVANTAGE LOW PROFILE HD DUMP DUMP TRAILER

	6'x12'	6'x14'
Model #	P126812LPHDT	P146814LPHDT
GVWR (lb.)	12000	14000
GAWR (lb. / Axle)	6000	7000
Curb Weight	3220	3560
Payload	8780	10440
Frame	6" x 2" x 3/16" Rec. Tube	
Crossmembers	3" Channel	
Tongue	5" Channel	
Coupler	Adjustable 2-5/16" Ball Coupler or Pintle Ring	
Jack	7K Bolt-On Drop Leg Jack	12K Bolt-On Drop Leg Jack
Fenders	Diamond Plate	
Axles	6,000 lb, Greased	7,000 lb, Greased
Suspension	Slipper Spring Suspension	
Tires	235/80R16 LRE	
Wheels	16"	
Volume Capacity	5.2 cu yd	6 cu yd
Lights	LED Lights - Rubber Mounted	
Electric Plug	7-Way SAE Plug	
Finish	PPG Industrial Polyurethane Paint	
Overall Length	198"	222"
Bed Width Inside	81.5"	
Bed Length Inside	144"	168"
Side Wall Height	20.5"	
Deck Height	28"	
Coupler Height	15" - 19"	
Gate	Triple-Acting Tailgate w/Chains	
Hydraulic Cylinder	Dual 3" x 36"	
Hydraulic Pump	12V Single Acting	
Battery	12V Deep-Cycle Battery	
Dump Angle	45°	43°

Specifications subject to change without notice.

