

ANGLE FRAME EQUIPMENT HAULER



ANGLE FRAME STANDARD FEATURES

Adjustable 2-5/16" Ball Coupler or Pintle Ring	Silver Wheels
Safety Chains	Epoxy Primer
7-Way SAE Plug	Polyurethane Paint Finish
Zip Breakaway System	Pressure-Treated Pine Decking (Oak on 8 Ton)
7K Bolt-On Drop Leg Jack (12K on 7 & 8 Ton)	Spare Tire Mount
5' Quick Release Ramps (Angle or Wood Filled)	D-Ring Tie Downs - 5/8" (6)
Diamond Plate Fenders	Stake Pockets (12)
EZ Lube Axles (Oil Bath on 8 Ton)	Aluminum Toolbox
Electric Brake Axles (2)	Sealed Wiring Harness
Nev-R-Adjust Brakes	LED Lights – Rubber Mounted
Slipper Spring Suspension	Three Year Warranty

Specifications subject to change without notice.



SPECIFICATIONS PAGE

ANGLE FRAME EQUIPMENT HAULER

	12K	14K	16K
Model #	P6CAM18	P7CAM18	P8CAM18
GVWR (lb.)	13200	15400	17600
GAWR (lb. / Axle)	6000	7000	8000
Curb Weight	2960	3200	3810
Payload	10240	12200	13790
Frame	6"x4"x5/16" Angle	6"x4"x3/8" Angle	6"x4"x1/2" Angle
Crossmembers	3" Channel		
Tongue	6" Channel @ 8.2 lb		6" Channel @ 10.5 lb
Coupler	Adjustable 2-5/16" Ball Coupler or Pintle Ring		
Jack	7K Bolt-On Drop Leg Jack	12K Bolt-On Drop Leg Jack	
Fenders	Diamond Plate		
Axles	6,000 lb, Greased	7,000 lb, Greased	8,000 lb, Oil Bath
Suspension	Slipper Spring Suspension		
Tires	235/80R16 LRE		215/75R17.5LRH
Wheels	16"		17.5"
Decking	Pressure-Treated Pine Decking		Oak Decking
Lights	LED Lights - Rubber Mounted		
Electric Plug	7-Way SAE Plug		
Finish	PPG Industrial Polyurethane Paint		
Overall Length / Flat	268" / 216"		
Deck Width	81"		
Deck Height	21"		
Coupler Height	17" - 21.5"		
Ramps	5' Quick Release Ramps		

Specifications subject to change without notice.

