

	18' 7K	18' 10K	20' 10K	22' 10K
Model #	P35CAM18CH	P5CAM18CH	P5CAM20CH	P5CAM22CH
GVWR (lb.)	7000	9900	9900	9900
GAWR (lb. / Axle)	3500	5080	5080	5080
Curb Weight	2000	2100	2250	2400
Payload	5000	7800	7650	7500
Frame	4" Channel	5" Channel		
Crossmembers	10 Gauge, Fabricated			
Tongue	4" Channel	5" Channel		
Coupler	Adjustable 2-5/16" Ball Coupler			
Jack	7K Bolt-On Drop Leg Jack			
Fenders	Diamond Plate			
Axles	3,500 lb. Greased	5,200 lb. Greased		
Suspension	Equalizer Leaf Spring, Double Eye			
Tires	205/75R15 LRC	225/75R15 LRD		
Wheels	15" Radial			
Decking	Pressure-Treated Pine Decking			
Lights	LED Lights - Rubber Mounted			
Electric Plug	7-Way SAE Plug			
Finish	Black PPG Polyurethane Industrial Paint			
Overall Length	258"		282"	306"
Bed Length Flat	172"		196"	220"
Beaver Tail Drop Length	44"		44"	
Between Fenders	82"		82"	
Deck Height	20.5"	22.5"	22.5"	22.5"
Coupler Height	14" - 22"			
Ramps	5' Steel Fabricated Ramps	5' Heavy Duty Ramps		

ADDITIONAL FEATURES

- Safety Chains
- Zip Breakaway System
- Spare Tire Mount
- D-Ring Tie-Downs - 1/2" (4)
- Stake Pockets (10)
- Sealed Wiring Harness
- Three Year Warranty

