



## SPECIFICATIONS PAGE

# CHANNEL FRAME EQUIPMENT HAULER



## CHANNEL FRAME STANDARD FEATURES

Adjustable 2-5/16" Ball Coupler or Pintle Ring  
Safety Chains  
7-Way SAE Plug  
Zip Breakaway System  
7K Bolt-On Drop Leg Jack (12K on 7 & 8 Ton)  
5' Quick Release Ramps (Angle or Wood Filled)  
Diamond Plate Fenders  
EZ Lube Axles  
Electric Brake Axles (2)  
Slipper Spring Suspension  
Silver Wheels

Epoxy Primer  
Polyurethane Paint Finish  
Pressure-Treated Pine Decking (Oak on 8 Ton)  
Spare Tire Mount  
D-Ring Tie Downs - 5/8" (6)  
Stake Pockets (12)  
Aluminum Toolbox  
Sealed Wiring Harness  
LED Lights - Rubber Mounted  
Three Year Warranty

Specifications subject to change without notice.





# SPECIFICATIONS PAGE

## CHANNEL FRAME EQUIPMENT HAULER

	12K	14K	16K
<b>Model #</b>	P6CAM18C	P7CAM18C	P8CAM18C
<b>GVWR (lb.)</b>	13200	15400	17600
<b>GAWR (lb. / Axle)</b>	6000	7000	8000
<b>Curb Weight</b>	2960	3200	3810
<b>Payload</b>	10240	12200	13790
<b>Frame</b>	6" Channel @ 10.5 lb		
<b>Crossmembers</b>	3" Channel		
<b>Tongue</b>	6" Channel @ 8.2 lb		6" Channel @ 10.5 lb
<b>Coupler</b>	Adjustable 2-5/16" Ball Coupler or Pintle Ring		
<b>Jack</b>	7K Bolt-On Drop Leg Jack	12K Bolt-On Drop Leg Jack	
<b>Fenders</b>	Diamond Plate		
<b>Axles</b>	6,000 lb, Greased	7,000 lb, Greased	8,000 lb, Oil Bath
<b>Suspension</b>	Slipper Spring Suspension		
<b>Tires</b>	235/80R16 LRE		215/75R17.5 LRH
<b>Wheels</b>	16"		17.5"
<b>Decking</b>	Pressure-Treated Pine Decking		Oak Decking
<b>Lights</b>	LED Lights - Rubber Mounted		
<b>Electric Plug</b>	7-Way SAE Plug		
<b>Finish</b>	PPG Industrial Polyurethane Paint		
<b>Overall Length / Flat</b>	268" / 216"		
<b>Deck Width</b>	81"		
<b>Deck Height</b>	21"		
<b>Coupler Height</b>	17" -21.5"		
<b>Ramps</b>	5' Quick Release Ramps		

Specifications subject to change without notice.

