

## **DECKOVER TRAILERS**

### **STANDARD DUTY**

	[	8.5 x 20	8.5 x 22	8.5 x 24		
Model #	Bumper Pull	PSD010220-BP-154	PSD010222-BP-154	PSD010224-BP-154		
	Gooseneck	PSD010220-GN-154	PSD010222-GN-154	PSD010224-GN-154		
GVWR (lbs)		15400	15400	15400		
GAWR (lbs/axle)		7000	7000	7000		
Curb Weight	Bumper Pull	2685	3070	3457		
	Gooseneck	3490	3870	4257		
Payload	Bumper Pull	12715	12330	11943		
	Gooseneck	11910	11530	11143		
Main Frame		W10 x 12#/ft., I-Beam				
Side Rails		5" C-Channel				
Cross Members		3" C-Channel (16" On-Center)				
Coupler	Bumper Pull	Adjustable 2-5/16" Ball Coupler				
	Gooseneck	Adjustable 2-5/16" Gooseneck Coupler				
Jack	Bumper Pull	Setback HD 12K Drop Leg Jack				
	Gooseneck	Dual Setback HD 12K Drop Leg Jacks with Toolbox (Between Uprights), Tool Tray and Winch Receiver Tube (In Neck)				
Axles		Easy Lube Hubs with Brakes				
Suspension		Slipper Spring				
Tires		235/80R16 LRE				
Wheels		16", 8 on 6.5, Radial				
Decking		2 x 8 Pressure Treated Pine				
Lights		All LED Lights				
Electric Plug		7-Way RV-Style Molded Plug				
Finish		PPG Industrial Polyurethane Paint				
Overall Length	Bumper Pull	290"	314"	338"		
	Gooseneck	348"	372"	396		
Deck Height		36″	36"	36"		
Coupler Height	Bumper Pull	Adjustable 21"-29"				
	Gooseneck	Adjustable 31" - 39-3/4"				
Ramps		8' Slide-In Fabricated Ramps				

Additional configurations available. Refer to the dealer portal or contact your sales representative for more information.



HD Steel Bulkhead Safety Chains Zip Breakaway System Spare Tire Mount D-Ring Tie Downs (6) Stake Pockets and Rub Rail Sealed Wiring Harness Three Year Warranty









Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.



# **DECKOVER TRAILERS**

### **STANDARD DUTY BEAVERTAIL**

		8.5 x 18 + 4	8.5 x 20 + 4	8.5 x 22 + 4		
Model #	Bumper Pull	PSD0102184-BP-154	PSD0102204-BP-154	PSD0102224-BP-154		
	Gooseneck	PSD0102184-GN-154	PSD0102204-GN-154	PSD0102224-GN-154		
GVWR (lbs)		15400	15400	15400		
GAWR (lbs/axle)		7000	7000	7000		
Curb Weight	Bumper Pull	3130	3475	3825		
	Gooseneck	3930	4275	4625		
Payload	Bumper Pull	12270	11925	11575		
	Gooseneck	11470	11125	10775		
Main Frame		W10 x 12#/ft., I-Beam				
Side Rails		5" C-Channel				
Cross Members		3" C-Channel (16" On-Center)				
Coupler	Bumper Pull	Adjustable 2-5/16" Ball Coupler				
	Gooseneck	Adjustable 2-5/16" Gooseneck Coupler				
Jack	Bumper Pull	Setback HD 12K Drop Leg Jack				
	Gooseneck	Dual Setback HD 12K Drop Leg Jacks with Toolbox (Between Uprights), Tool Tray and Winch Receiver Tube (In Neck)				
Axles		Easy Lube Hubs with Brakes				
Suspension		Slipper Spring				
Tires		235/80R16 LRE				
Wheels		16", 8 on 6.5, Radial				
Decking		2 x 8 Pressure Treated Pine				
Lights		All LED Lights				
Electric Plug		7-Way RV-Style Molded Plug				
Finish		PPG Industrial Polyurethane Paint				
Overall Length	Bumper Pull	323"	347"	371"		
	Gooseneck	371"	395"	419"		
Deck Height		36"	36"	36"		
Coupler Height	Bumper Pull	Adjustable 21" - 29"				
	Gooseneck	Adjustable 31" - 39.75"				
Ramps		5ft. 4" HD Channel Spring-Assist Standup Ramps with Adjustable Support Legs				

Additional configurations available. Refer to the dealer portal or contact your sales representative for more information.

#### **ADDITIONAL FEATURES**

HD Steel Bulkhead Safety Chains Zip Breakaway System Spare Tire Mount D-Ring Tie Downs (6) Stake Pockets and Rub Rail Sealed Wiring Harness Three Year Warranty



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.