



DECKOVER TRAILERS

THE BEAST AIR BRAKE

	20' + 5' 30.7K	20' + 5' 51.7K	24' + 5' 65K
Model #	P12CAM8205TA	P20CAM8205TA	P25CAM8245TA
GVWR (lb.)	30725	51750	65000
GAWR (lb. / Axle)	12000	22500	22500
Curb Weight	6725	9095	11575
Payload	24000	42655	53425
Main Frame	12" I-Beam @ 16 lb	14" I-Beam @ 22 lb	
Crossmembers	3" Channel	5" Channel	
Side Rail	6" Channel @ 8.2 lb	8" Channel @ 11.5 lb	
Tongue	12" I-Beam @ 16 lb	14" I-Beam @ 22 lb	
Beavertail	5' Beavertail		
Coupler	Adjustable Pintle Ring		
Jack	Dual 12K Bolt-On Drop Leg 2-Speed Jacks	Dual 25K Bolt-On Drop Leg 2-Speed Jacks	
Axles	Oil Bath Axles		
Suspension	Slipper Spring Suspension	Hutch H-9700 Suspension	
Tires	235/80R16 LRE Dual	235/75R17.5 LRH Dual	
Wheels	16" Dual	17.5"	
Decking	Nominal 2" Oak Deck		
Lights	LED Lights - Rubber Mounted		
Electric Plug	Sealed 7 Pin Plug w/Arctic Flex Whip		
Finish	PPG Industrial Polyurethane Paint		
Overall Length	376"	376"	424"
Deck Height	34"	35"	
Coupler Height	22" - 30"	21.5" - 30.5"	
Ramps	5' Bi-Directional Spring Assisted Wood Filled Ramps		

Additional configurations available. Refer to the dealer portal or contact your sales representative for more information.

Dealer Notes

These are the minimum length requirements for the following trailer and option combinations: Air Brake Models

40" x 80" Ramps - At least 22' Flat w/ 5' Beavertail

40" x 80" Ramps w/ Double-Break Beavertail - At least 24' Flat plus Double-Break Beavertail.

40" x 142" Bi-Fold Ramps - At least 24' Flat w/ 5' Beavertail.

ADDITIONAL FEATURES

- Full Pierced Beam Construction
- Safety Chains (1/2" High Test)
- D-Ring Tie-Downs - 3/4" (12)
- Toolbox
- Mud Flaps
- Steps (4)
- Sealed Wiring Harness
- Three Year Warranty



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.