

DUMP TRAILERS

STANDARD DUTY LOW PROFILE

| | 6' x 10' 7K | 6' x 10' 10K | 6' x 12' 10K |
|---------------------------|-----------------------------------|-------------------|-----------------|
| Model # | PSDD7210-BP-070 | PSDD7210-BP-100 | PSDD7212-BP-100 |
| GVWR (lb.) | 7000 | 9900 | 9900 |
| GAWR (lb. / Axle) | 3500 | 5200 | 5200 |
| Curb Weight | 2900 | 3000 | 3220 |
| Payload | 4100 | 6900 | 6680 |
| Crossmembers | 3" Fabricated C-Channel | | |
| Tongue | 5" Channel | | |
| Coupler | Adjustable 2-5/16" Ball Coupler | | |
| Jack | 7K Bolt-On Drop Leg Jack | | |
| Fenders | Tread Plate | | |
| Axles | 3,500 lb. Greased | 5,200 lb. Greased | |
| Suspension | Double Eye Suspsension | | |
| Tires | 205/75R15 LRC | 225/75R15 LRD | |
| Wheels | 15", 5 on 4.5 | 15", 6 on 5.5 | |
| Volume Capacity | 3.9 cu yd. | 3.9 cu yd. | 4.6 cu yd. |
| Lights | LED Lights - Rubber Mounted | | |
| Electric Plug | 7-Way SAE Plug | | |
| Finish | PPG Industrial Polyurethane Paint | | |
| Overall Length | 164" | 164" | 188" |
| Bed Width Inside | 72.5" | | |
| Bed Length Inside | 120" | 120" | 144" |
| Side Wall Height | 20.5" | | |
| Deck Height | 26" | 26" 28" | |
| Coupler Height | 14" - 20" | | |
| Gate | Triple-Acting Tailgate w/Chains | | |
| Hydraulic Cylinder | Single 3" x 30" Single 4x30" | | |
| Hydraulic Pump | 12V Power Up, Power Down | | |
| Battery | 12V Deep-Cycle Battery DP24 | | |
| Dump Angle | 49° | 49° | 49° |

ADDITIONAL FEATURES

Safety Chains Zip Breakaway System Slide-Out Ladder Ramps (6') 10-Gauge Floor 12-Gauge Sides Spare Tire Mount D-Ring Tie-Downs - 1/2" (4) 2" x 4" Stake Pockets Rub Rail Integrated Tarp Shroud Sealed Wiring Harness Steel Lockable Pump Box Remote Control with 20' Cord Three Year Warranty







