

ANGLE FRAME

		15.4K	17.6K
Model #	16'	P7CAM16	P8CAM16
	18'	P7CAM18	P8CAM18
	20'	P7CAM20	P8CAM20
GVWR (lb.)		15400	17600
GAWR (lb. / Axle)		7000	8000
Curb Weight	16'	2960	3550
	18'	3200	3810
	20'	3440	4070
Payload	16'	12440	14050
	18'	12200	13790
	20'	11960	13530
Frame		6"x4"x3/8" Angle	6"x4"x1/2" Angle
Crossmembers		3" Channel	
Tongue		6" Channel @ 10.5 lb	
Coupler		Adjustable 2-5/16" Ball Coupler	
Jack		12K Bolt-On Drop Leg Jack	
Fenders		Diamond Plate	
Axles		7,000 lb. Greased	8,000 lb. Oil Bath
Suspension		Slipper Spring Suspension	
Tires		235/80R16 LRE	215/75R17.5LRH
Wheels		16" 8 on 6.5	17.5" 8 on 6.5
Decking		Pressure-Treated Pine Decking	Oak Decking
Lights		LED Lights - Rubber Mounted	
Electric Plug		7-Way SAE Plug	
Finish		PPG Industrial Polyurethane Paint	
Overall Length / Flat	16'	244"/192"	
	18'	268"/216"	
	20'	292"/240"	
Deck Width		81"	
Deck Height		21"	
Coupler Height		17" - 21.5"	
Ramps		5' Quick Release Ramps with Adjustable Stabilizer Legs	

Additional configurations available. Refer to the dealer portal or contact your sales representative for more information.

ADDITIONAL FEATURES

- Safety Chains
- Zip Breakaway System with Solar Charger
- Spare Tire Mount
- D-Ring Tie Downs - 5/8" (6)
- Stake Pockets (12)
- Steel Toolbox
- Sealed Wiring Harness
- Three Year Warranty

