

## **EQUIPMENT TRAILERS**

## **CHANNEL FRAME**

		15.4K	17.6K
Model #	16'	P7CAM16C	P8CAM16C
	18'	P7CAM18C	P8CAM18C
	20'	P7CAM20C	P8CAM20C
GVWR (lb.)		15400	17600
GAWR (lb. / Axle)		7000	8000
Curb Weight	16'	2960	3550
	18'	3200	3810
	20'	3440	4070
Payload	16'	12440	14050
	18'	12200	13790
	20'	11960	13530
Frame		6" Channel @ 10.5 lb	
Crossmembers		3" Channel	
Tongue		6" Channel @ 8.2 lb	6" Channel @ 10.5 lb
Coupler		Adjustable 2-5/16" Ball Coupler	
Jack		12K Bolt-On Drop Leg Jack	
enders		Diamond Plate	
Axles		7,000 lb. Greased	8,000 lb. Oil Bath
Suspension		Slipper Spring Suspension	
Tires		235/80R16 LRE	215/75R17.5 LRH
Wheels		16" 8 on 6.5	17.5" 8 on 6.5
Decking		Pressure-Treated Pine Decking	Oak Decking
Lights		LED Lights - Rubber Mounted	
Electric Plug		7-Way SAE Plug	
Finish		PPG Industrial Polyurethane Paint	
Overall Length / Flat	16'	244"/192"	
	18'	268"/216"	
	20'	292"/240"	
Deck Width		81"	
Deck Height		21"	
Coupler Height		17" -21.5"	
Ramps		5' Quick Release Ramps	
Additional and among the Defends the declarated as a set of a company to the company of the comp			

Additional configurations available. Refer to the dealer portal or contact your sales representative for more information.

## **ADDITIONAL FEATURES**

Safety Chains Zip Breakaway System with Solar Charger Spare Tire Mount D-Ring Tie Downs - 5/8" (6) Stake Pockets (12) Steel Toolbox Sealed Wiring Harness Three Year Warranty







