



## SPECIFICATIONS PAGE

# LOW PROFILE DUMP TRAILER



## LOW PROFILE DUMP STANDARD FEATURES

Tubular Main Frame  
Adjustable 2-5/16" Ball Coupler or Pintle Ring  
Safety Chains  
7-Way SAE Plug  
Breakaway Switch  
Charge Wire with Circuit Breaker  
7K Bolt-On Drop Leg Jack  
Slide-Out Ladder Ramps (6')  
Triple-Acting Tailgate w/ Chains  
Diamond Plate Fenders  
EZ Lube Axles  
Electric Brake Axles (2)  
Nev-R-Adjust Brakes  
Slipper Spring Suspension  
Silver Wheels

Epoxy Primer  
Polyurethane Paint Finish  
10-Gauge Floor  
12-Gauge Sides  
Spare Tire Mount  
D-Ring Tie-Downs - 1/2" (4)  
2" x 4" Full Height Stake Pockets  
Tie Down Rail  
Sealed Wiring Harness  
LED Lights – Rubber Mounted  
Aluminum Lockable Pump Box  
Remote Control with 20' Cord  
12V Deep-Cycle Battery  
110V Battery Charger  
Three Year Warranty

*Specifications subject to change without notice.*





# SPECIFICATIONS PAGE

## LOW PROFILE DUMP TRAILER

	72.5" x 10'	72.5" x 12'
Model #	P5CAM610LPD	P5CAM612LPD
GVWR (lb.)	11960	11960
GAWR (lb. / Axle)	5200	5200
Curb Weight	2600	2820
Payload	9360	9140
Frame	6" x 2" x 3/16" rec tube	
Crossmembers	3" Channel	
Tongue	5" Channel	
Coupler	Adjustable 2-5/16" Ball Coupler or Pintle Ring	
Jack	7K Bolt-On Drop Leg Jack	
Fenders	Diamond Plate	
Axles	5,200 lb, Greased	
Suspension	Equalized Slipper Spring Suspension	
Tires	225/75R15 LRD	
Wheels	15"	
Volume Capacity	3.9 cu yd.	4.6 cu yd.
Lights	LED Lights - Rubber Mounted	
Electric Plug	7-Way SAE Plug	
Finish	PPG Industrial Polyurethane Paint	
Overall Length	164"	188"
Bed Width Inside	72.5"	
Bed Length Inside	120"	144"
Side Wall Height	20.5"	
Deck Height	28"	
Coupler Height	17.5" - 24.25"	
Gate	Triple-Acting Tailgate w/Chains	
Hydraulic Cylinder	One 3.5" x 36"	One Telescopic
Hydraulic Pump	12V Single Acting	
Battery	12V Deep-Cycle Battery	
Dump Angle	48°	46°

Specifications subject to change without notice.

