



SPECIFICATIONS PAGE

STANDARD DUTY DECKOVER TRAILER



STANDARD DUTY DECKOVER STANDARD FEATURES

Adjustable 2-5/16" Ball Coupler or Pintle Ring
Safety Chains
7-Way SAE Plug
Zip Breakaway System
7K Bolt-On Drop Leg Jack
6' Adjustable Spring-Assisted Ladder Ramps
EZ Lube Axles
Electric Brakes Axles (2)
Nev-R-Adjust Brakes
Slipper Spring Suspension
Silver Wheels

Epoxy Primer
Polyurethane Paint Finish
Pressure-Treated Pine Decking (Oak on 8 Ton)
Spare Tire Mount
Stake Pockets and Rub Rail
Aluminum Toolbox
Mud Flaps
Sealed Wiring Harness
LED Lights – Rubber Mounted
Three Year Warranty

Specifications subject to change without notice.



STANDARD DUTY DECKOVER TRAILER

	12K	14K	16K
Model #	P6CAM8164DO	P7CAM8164DO	P8CAM8164DO
GVWR (lb.)	13200	15400	17600
GAWR (lb. / Axle)	6000	7000	8000
Curb Weight	3620	3720	4190
Payload	9580	11680	13410
Main Frame	8" I-Beam @ 10 lbs.		8" I-Beam @ 13 lbs.
Crossmembers	3" Channel		
Side Rail	5" Channel		
Tongue	8" I-Beam @ 10 lbs.		8" I-Beam @ 13 lbs.
Beavertail	4'		
Coupler	Adjustable 2-5/16" Ball Coupler or Pintle Ring		
Jack	7K Bolt-On Drop Leg Jack		12K Bolt-On Drop Leg Jack
Axles	6,000 lb, Greased	7,000 lb, Greased	8,000 lb, Oil Bath
Suspension	Slipper Spring Suspension		
Tires	235/80R16 LRE		215/75R17.5 LRH
Wheels	16" Spoke		17.5" Mod
Decking	Pressure-Treated Pine Decking		Oak Decking
Lights	LED Lights - Rubber Mounted		
Electric Plug	7-Way SAE Plug		
Finish	PPG Industrial Polyurethane Paint		
Overall Length	296"		
Deck Height	34"	35"	
Coupler Height	21" - 30"		22" - 31"
Ramps	6' Adjustable Spring Assisted Ramps		



Specifications subject to change without notice.