

		15.4K	17.6K
Model #	15+4	P7CAM154STT	P8CAM154STT
	16+4	P7CAM164STT	P8CAM164STT
	17+4	P7CAM174STT	P8CAM174STT
GVWR (lb.)		15400	17600
GAWR (lb. / Axle)		7000	8000
Curb Weight	15+4	3500	4230
	16+4	3610	4350
	17+4	3720	4470
Payload	15+4	11900	13370
	16+4	11790	13250
	17+4	11680	13130
Frame		6"x4"x3/8" Angle	6"x4"x1/2" Angle
Crossmembers		3" Channel	
Tongue		6" Channel @ 10.5 lb	
Coupler		Adjustable 2-5/16" Ball Coupler	
Jack		12K Bolt-On Drop Leg Jack	
Fenders		Diamond Plate	
Axles		7,000 lb. Greased	8,000 lb. Oil Bath
Suspension		Slipper Spring Suspension	
Tires		235/80R16 LRE	215/75R17.5 LRH
Wheels		16", 8 on 6.5	17.5", 8 on 6.5
Decking		Pressure-Treated Pine Decking	Oak Decking
Lights		LED Lights - Rubber Mounted	
Electric Plug		7-Way SAE Plug	
Finish		PPG Industrial Polyurethane Paint	
Overall Length	15+4	280"	
	16+4	304"	
	17+4	328"	
Between Fenders		81"	
Deck Height		17"	22"
Coupler Height		14" - 18.5"	19" - 23.5"
Tilt Angle		11°	13°

Additional configurations available. Refer to the dealer portal or contact your sales representative for more information.

ADDITIONAL FEATURES

- Safety Chains
- Zip Breakaway System with Solar Charger
- 4" Drop Axles
- Spare Tire Mount
- (8) D-Ring Tie Downs - 5/8" (4 Stat., 4 Tilt)
- Stake Pockets (6)
- Pallet Fork Carrier (N/A w/Gooseneck)
- Steel Toolbox
- Banjo Eye Tie-Downs (2)
- Sealed Wiring Harness
- Adjustable Hydraulic Cushion Cylinder
- Three Year Warranty

