



## SPECIFICATIONS PAGE

# 10, 12, and 15 TON HEAVY DUTY DECKOVER TRAILER



## 10, 12, and 15 TON HD DECKOVER STANDARD FEATURES

Steel Plated Tongue  
Full Pierced Beam Construction  
Adjustable Pintle Hitch  
Safety Chains (1/2" High Test)  
7-Way SAE Plug (Electric)  
7-Way Pin Plug (Air)  
Zip Breakaway System  
Dual 12K 2-Speed Jacks (Bolt-On)  
Oil Bath Axles  
Adjustable Slipper Spring Suspension  
Hutch H-9700 Suspension  
Silver Wheels

Epoxy Primer  
Polyurethane Paint Finish  
Nominal 2" Oak Deck  
Spare Tire Mount (Under Bed)  
D-Ring Tie-Downs - 3/4" (12)  
Toolbox  
Mud Flaps  
Steps (4)  
Sealed Wiring Harness  
LED Lights – Rubber Mounted  
Three Year Warranty

*Specifications subject to change without notice.*





## SPECIFICATIONS PAGE

# 10, 12, and 15 TON HEAVY DUTY DECKOVER TRAILER

|                   | 20' + 5' (Electric)                                 | 20' + 5' (Electric) | 20' + 5' (Air) | 20' + 5' (Electric)   |
|-------------------|-----------------------------------------------------|---------------------|----------------|-----------------------|
| Model #           | P10CAM8205TE                                        | P12CAM8205TE        | P12CAM8205TA   | P15CAM8205TE          |
| GVWR (lb.)        | 26450                                               | 30650               | 30725          | 37500                 |
| GAWR (lb. / Axle) | 10000                                               | 12000               | 12000          | 15000                 |
| Curb Weight       | 6450                                                | 6650                | 6725           | 7500                  |
| Payload           | 20000                                               | 24000               | 24000          | 30000                 |
| Main Frame        | 12" I-Beam @ 16 lb                                  |                     |                | 12" I-Beam @ 22 lb    |
| Crossmembers      | 3" Channel                                          |                     |                |                       |
| Side Rail         | 6" Channel @ 8.2 lb                                 |                     |                |                       |
| Tongue            | 12" I-Beam @ 16 lb                                  |                     |                | 12" I-Beam @ 22 lb    |
| Beavertail        | 5' Beavertail                                       |                     |                |                       |
| Coupler           | Adjustable Pintle Ring                              |                     |                |                       |
| Jack              | Dual 12K Bolt-On Drop Leg 2-Speed Jacks             |                     |                |                       |
| Axles             | Oil Bath                                            |                     |                |                       |
| Suspension        | Adjustable Slipper Spring Suspension                |                     |                |                       |
| Tires             | 235/80R16 LRE Dual                                  |                     |                | 215/75R 17.5 LRE Dual |
| Wheels            | 16" Dual                                            |                     |                | 17.5" Dual            |
| Decking           | Nominal 2" Oak Decking                              |                     |                |                       |
| Lights            | LED Lights - Rubber Mounted                         |                     |                |                       |
| Electric Plug     | 7-Way SAE Plug                                      |                     | 7-Way Pin Plug | 7-Way SAE Plug        |
| Finish            | PPG Industrial Polyurethane Paint                   |                     |                |                       |
| Overall Length    | 376"                                                |                     |                |                       |
| Deck Height       | 34"                                                 |                     |                | 35"                   |
| Coupler Height    | 22" - 30"                                           |                     |                | 23" - 31"             |
| Ramps             | 5' Bi-Directional Spring Assisted Wood Filled Ramps |                     |                |                       |

Specifications subject to change without notice.

