



SPECIFICATIONS PAGE

FULL DECK TILT TRAILER



FULL DECK TILT STANDARD FEATURES

Adjustable 2-5/16" Ball Coupler or Pintle Ring
Safety Chains
7-Way SAE Plug
Zip Breakaway System
7K Bolt-On Drop Leg Jack (12K on 7 & 8 Ton)
Diamond Plate Fenders
EZ Lube Axles 4" Drop
Electric Brake Axles (2)
Nev-R-Adjust Brakes
Slipper Spring Suspension
Silver Wheels
Epoxy Primer

Polyurethane Paint Finish
Pressure-Treated Pine Decking (Oak on 8 Ton)
Spare Tire Mount
D-Ring Tie Downs - 5/8" (6)
Stake Pockets (8)
Aluminum Toolbox
Banjo Eye Tie-Downs (2)
Sealed Wiring Harness
LED Lights - Rubber Mounted
Adjustable Hydraulic Cushion Cylinder
Three Year Warranty

Specifications subject to change without notice.





SPECIFICATIONS PAGE

FULL DECK TILT TRAILER

	10K	12K	14K	16K
Model #	P5CAM18FTT	P6CAM18FTT	P7CAM18FTT	P8CAM18FTT
GVWR (lb.)	11960	13800	16100	18400
GAWR (lb. / Axle)	5080	6000	7000	8000
Curb Weight	2980	3080	3280	3990
Payload	8980	10720	12820	14410
Frame	6"x4"x5/16" Angle		6"x4"x3/8" Angle	6"x4"x1/2" Angle
Crossmembers	3" Channel			
Tongue	6" Channel @ 8.2 lbs.		6" Channel @ 10.5 lbs.	
Coupler	Adjustable 2-5/16" Ball Coupler or Pintle Ring			
Jack	7K Bolt-On Drop Leg Jack		12K Bolt-On Drop Leg Jack	
Fenders	Diamond Plate			
Axles	5,000 lb, Greased	6,000 lb, Greased	7,000 lb, Greased	8,000 lb, Oil Bath
Suspension	Slipper Spring Suspension			
Tires	225/75R15 LRD	235/80R16 LRE		215/75R17.5 LRH
Wheels	15" Spoke	16" Spoke		17.5" Mod
Decking	Pressure-Treated Pine Decking			Oak Decking
Lights	LED Lights - Rubber Mounted			
Electric Plug	7-Way SAE Plug			
Finish	PPG Industrial Polyurethane Paint			
Length	268"			
Between Fenders	81"			
Deck Height	16"	17"		22"
Coupler Height	13" - 17.5"	14" - 18.5"		19" - 23.5"
Load Angle	8°	9°		11°

Specifications subject to change without notice.

