



UTILITY TRAILERS

TANDEM AXLE

	7' x 14' 7K	7' x 16' 7K	7' x 18' 7K	7' x 16' 10K	7' x 18' 10K	7' x 20' 10K
Model #	PUTT8214-BP-070	PUTT8216-BP-070	PUTT8218-BP-070	PUTT8216-BP-100	PUTT8218-BP-100	PUTT8220-BP-100
GVWR (lb.)	7000	7000	7000	9900	9900	9900
GAWR (lb. / Axle)	3500	3500	3500	5200	5200	5200
Curb Weight	1700	1900	2200	2290	2440	2540
Payload	5300	5100	4800	7610	7460	7360
Frame	3 x 2 x 1/4 Angle		4 x 3 x 1/4 Angle	5 x 3 x 1/4" Angle		
Crossmembers	3 x 2 x 3/16 Angle (24" On-Center)			3 x 2 x 3/16" Angle		
Top Rail	2 x 2 Square Tube			3 x 2 Rectangular Tube		
Tongue	4" Channel (A-Frame)			5" Channel (A-Frame)		
Uprights	2 x 2 square Tube			2 x 2 square Tube		
Coupler	2-5/16" Ball			2-5/16" Ball		
Jack	2K, Set Back			7K Bolt-On Drop Leg Jack		
Fenders	Diamond Plate					
Axles	Cambered Brake (Both Axles)					
Suspension	Equalized Leaf Spring					
Tires	205/75R15 LRC			225/75R15 LRD		
Wheels	15", 5 on 4.5			15", 6 on 5.5		
Decking	2 x 6 Pressure Treated Pine					
Lights	All LED Lights					
Electric Plug	7 Pole RV Molded Flat Blade					
Finish	PPG Industrial Polyurethane Paint					
Overall Length	215"	239"	263"	239"	270"	294"
Bed Length	168"	192"	216"	192"	216"	240"
Bed Width	81.5"	81.5"	81.5"	81.5"	81.5"	81.5"
Deck Height	18"	18"	18"	20"	20"	20"
Coupler Height	16"	16"	16"	14.5" - 23.5"	14.5" - 23.5"	14.5" - 23.5"
Gate	4' Landscape Gate, Spring Assisted			5' Reinforced (Ladder Style) Landcptae Gate, Spring Assisted		

ADDITIONAL FEATURES

- Safety Chains
- Zip Breakaway System
- Spare Tire Mount
- Rub Rail
- Sealed Harness
- Enclosed Wiring
- Three Year Warranty



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.