

10K TANDEM AXLE UTILITY TRAILER



10K TANDEM AXLE UTILITY STANDARD FEATURES

Tube Uprights and Top Railing
 Adjustable 2-5/16" Ball Coupler or Pintle Ring
 Zip Breakaway System
 7K Set-Back Jack
 4' Spring-Assist Laydown Gate
 Diamond Plate Fenders
 Electric Brake Axles (2)
 Radial Tires
 Silver Wheels

Epoxy Primer
 Polyurethane Paint Finish
 Pressure-Treated Pine Decking
 Spare Tire Mount
 Rub Rail
 Sealed Harness
 LED Lights – Rubber Mounted
 Three Year Warranty

Specifications subject to change without notice.



SPECIFICATIONS PAGE

10K TANDEM AXLE UTILITY TRAILER

	7x18	7x20
Model #	P8218TAT-B-100	P8220TAT-B-100
GVWR (lb.)	9900	9900
GAWR (lb. / Axle)	5200	5200
Curb Weight	2440	2540
Payload	7460	7360
Frame	5 x 3 x 1/4" Angle	
Crossmembers	3 x 2 x 3/16" Angle	
Top Rail	2 x 2 Square Tube	
Tongue	5" Channel (A-Frame)	
Uprights	2 x 2 square Tube	
Coupler	2-5/16" Ball	
Jack	7K Bolt-On Drop Leg Jack	
Fenders	Diamond Plate	
Axles	5200lb Greased	
Suspension	Equalized Leaf Spring	
Tires	225/75R15 LRD	
Wheels	15" Spoke	
Decking	2 x 8 Pressure Treated Pine	
Lights	All LED Lights	
Electric Plug	7 Pole RV Molded Flat Blade	
Finish	Black PPG Polyurethane Industrial Paint	
Overall Length	270"	294"
Bed Length	216"	240"
Bed Width	81.5"	81.5"
Deck Height	20"	20"
Coupler Height	14.5" - 23.5"	14.5" - 23.5"
Gate	2 x 2 Tube, Mesh Covered, Full Width Spring Assist Ramp Gate with Handle	

Specifications subject to change without notice.

