



## SPECIFICATIONS PAGE

# UTILITY TRAILERS

## SINGLE AXLE



### UTILITY STANDARD FEATURES

LED Lights  
Sealed Harness  
Enclosed Wiring  
4' Spring Assist Laydown Gate  
Set Back Jack  
Tube Uprights and Top Railing  
Powder Coat

Bead Blasted Structure  
Rub Rail  
Radial Tires  
Spare Tire Mount  
Diamond Plate Fenders  
Three Year Warranty

*Specifications subject to change without notice.*





# SPECIFICATIONS PAGE

## UTILITY TRAILERS SINGLE AXLE

	5'x10'	6'x10'	6'x12'	7'x12'
<b>Model #</b>	P6210TA-B-030	P7210TA-B-030	P7212TA-B-030	P8212TA-B-030
<b>GVWR (lb.)</b>	2990	2990	2990	2990
<b>GAWR (lb. / Axle)</b>	3500	3500	3500	3500
<b>Curb Weight</b>	960	990	1115	1300
<b>Payload</b>	2030	2000	1875	1690
<b>Frame</b>	3 x 2 x 3/16 Angle			
<b>Crossmembers</b>	3 x 2 x 3/16 Angle (24" On-Center)			
<b>Top Rail</b>	2 x 2 Square Tube			
<b>Tongue</b>	3" Channel (A-Frame)			
<b>Uprights</b>	2 x 2 square Tube			
<b>Coupler</b>	2" Ball			
<b>Jack</b>	2K Zinc Plated, Set Back			
<b>Fenders</b>	Diamond Plate			
<b>Axles</b>	Cambered Idler			
<b>Suspension</b>	Leaf Spring			
<b>Tires</b>	205/75R15 LRC			
<b>Wheels</b>	15", 5 on 4.5, Radial Tires			
<b>Decking</b>	2 x 6 Pressure Treated Pine			
<b>Lights</b>	All LED Lights			
<b>Electric Plug</b>	4 Way Flat			
<b>Finish</b>	Powder Coated High Gloss Black			
<b>Overall Length</b>	161"	161"	185"	185"
<b>Bed Length</b>	120"	120"	144"	144"
<b>Bed Width</b>	61.5"	71.5"	71.5"	81.5"
<b>Deck Height</b>	18"	18"	18"	18"
<b>Coupler Height</b>	16"	16"	16"	16"
<b>Gate</b>	2 x 2 Tube, Mesh Covered, Full Width Spring Assist Ramp Gate with Handle			

Specifications subject to change without notice.

