



SPECIFICATIONS PAGE

UTILITY TRAILERS

TANDEM AXLE



UTILITY STANDARD FEATURES

Electric Brakes
LED Lights
Sealed Harness
Enclosed Wiring
4' Spring Assist Laydown Gate
Set Back Jack
Tube Uprights and Top Railing

Powder Coat
Bead Blasted Structure
Rub Rail
Radial Tires
Spare Tire Mount
Diamond Plate Fenders
Three Year Warranty



Specifications subject to change without notice.

800.378.7623 | CAMSUPERLINE.COM | © 2020 Novae Corp.



SPECIFICATIONS PAGE

UTILITY TRAILERS TANDEM AXLE

	7'x14'	7'x16'	7'x18'
Model #	P8214TAT-B-070	P8216TAT-B-070	P8218TAT-B-070
GVWR (lb.)	7000	7000	7000
GAWR (lb. / Axle)	3500	3500	3500
Curb Weight	1700	1900	2200
Payload	5300	5100	4800
Frame	3 x 2 x 1/4 Angle		4 x 3 x 1/4 Angle
Crossmembers	3 x 2 x 3/16 Angle (24" On-Center)		
Top Rail	2 x 2 Square Tube		
Tongue	4" Channel (A-Frame)		
Uprights	2 x 2 square Tube		
Coupler	2-5/16" Ball		
Jack	2K Zinc Plated, Set Back		
Fenders	Diamond Plate		
Axles	Cambered Brake (Both Axles)		
Suspension	Equalized Leaf Spring		
Tires	205/75R15 LRC		
Wheels	15", 5 on 4.5, Radial Tires		
Decking	2 x 6 Pressure Treated Pine		
Lights	All LED Lights		
Electric Plug	7 Pole RV Molded Flat Blade		
Finish	Powder Coated High Gloss Black		
Overall Length	215"	239"	263"
Bed Length	168"	192"	216"
Bed Width	81.5"	81.5"	81.5"
Deck Height	18"	18"	18"
Coupler Height	16"	16"	16"
Gate	2 x 2 Tube, Mesh Covered, Full Width Spring Assist Ramp Gate with Handle		

Specifications subject to change without notice.

