



SPECIFICATIONS PAGE

12'/14' FULL DECK TILT TRAILER



12'/14' FULL DECK TILT STANDARD FEATURES

Adjustable 2-5/16" Ball Coupler or Pintle Ring
Safety Chains
7-Way SAE Plug
Zip Breakaway System
7K Bolt-On Drop Leg Jack
Diamond Plate Fenders
EZ Lube Axles
Electric Brakes
Nev-R-Adjust Brakes
Slipper Spring Suspension
Silver Wheels

Epoxy Primer
Polyurethane Paint Finish
Pressure-Treated Pine Decking
Spare Tire Mount
D-Ring Tie-Downs - 5/8" (4)
Banjo Eye Tie-Downs (2)
Sealed Wiring Harness
LED Lights - Rubber Mounted
Adjustable Hydraulic Cushion Cylinder
Three Year Warranty

Specifications subject to change without notice.





SPECIFICATIONS PAGE

12'/14' FULL DECK TILT TRAILER

	10K	10K	10K
Model #	P5CAM612FTT	P5CAM712FTT	P5CAM714FTT
GVWR (lb.)	11000	11000	11000
GAWR (lb. / Axle)	5200	5200	5200
Curb Weight	2300	2350	2560
Payload	8700	8650	8440
Frame	6"x4"x5/16" Angle		
Crossmembers	3" Channel		
Tongue	6"x4"x5/16" Angle		
Coupler	Adjustable 2-5/16" Ball Coupler or Pintle Ring		
Jack	7K Bolt-On Drop Leg Jack		
Fenders	Diamond Plate		
Axles	5,200 lb, Greased		
Suspension	Slipper Spring Suspension		
Tires	225/75R15 LRD		
Wheels	15" Spoke		
Decking	Pressure-Treated Pine Decking		
Lights	LED Lights - Rubber Mounted		
Electric Plug	7-Way SAE Plug		
Finish	PPG Industrial Polyurethane Paint		
Overall Length	198"		222"
Between Fenders	75"	81"	
Deck Height	16"		
Coupler Height	14" - 20.75"		
Load Angle	11°		10°

Specifications subject to change without notice.

