



SPECIFICATIONS PAGE

FULL TILT DECKOVER TRAILER



FULL TILT DECKOVER STANDARD FEATURES

Steel Plated Tongue
Adjustable 2-5/16" Ball Coupler or Pintle Ring
Safety Chains
7-Way SAE Plug
Zip Breakaway System
12K Bolt-On Drop Leg Jack
Knife Edge Approach
Rear Impact Guard
EZ Lube Axles
Electric Brakes Axles (2)
Nev-R-Adjust Brakes
Slipper Spring Suspension
Silver Wheels

Epoxy Primer
Polyurethane Paint Finish
Pressure-Treated Pine Decking (Oak on 8 Ton)
Spare Tire Mount
D-Ring Tie Downs - 5/8"
Stake Pockets and Rub Rail
Aluminum Pump Box
Mud Flaps
Sealed Wiring Harness
LED Lights – Rubber Mounted
Power Up / Power Down
Dual Hydraulic Cylinders
Three Year Warranty

Specifications subject to change without notice.





SPECIFICATIONS PAGE

FULL TILT DECKOVER TRAILER

	14K	16K
Model #	P7CAM822D0TT	P8CAM822D0TT
GVWR (lb.)	15400	17600
GAWR (lb. / Axle)	7000	8000
Curb Weight	4280	4840
Payload	11120	12760
Main Frame	8" I-Beam @ 10 lbs.	8" I-Beam @ 13 lbs.
Crossmembers	3" Channel	
Side Rail	5" Channel @ 6.7 lb	
Tongue	8" I-Beam @ 10 lb	8" I-Beam @ 13 lb
Coupler	Adjustable 2-5/16" Ball Coupler or Pintle Ring	
Jack	12K Bolt-On Drop Leg Jack	
Axles	7,000 lb, Greased	8,000 lb, Oil Bath
Suspension	Slipper Spring Suspension	
Tires	235/80R16 LRE	215/75R17.5 LRH
Wheels	16" Spoke	17.5" Mod
Decking	Pressure-Treated Pine Decking	Oak Decking
Lights	LED Lights - Rubber Mounted	
Electric Plug	7-Way SAE Plug	
Finish	PPG Industrial Polyurethane Paint	
Overall Length / Flat	321" / 266"	
Deck Height	35"	36"
Coupler Height	20.5" - 29.5"	21.5" - 30.5"
Approach Plate	Knife Edge Approach	
Load Angle	16°	17°

Specifications subject to change without notice.

