



SPECIFICATIONS PAGE

FULL WIDTH EQUIPMENT HAULER



FULL WIDTH STANDARD FEATURES

Adjustable 2-5/16" Ball Coupler or Pintle Ring
Safety Chains
7-Way SAE Plug
Breakaway with Charger and Test Light
7K Bolt-On Drop Leg Jack (12K on 7 & 8 Ton)
5' Quick Release Angle Ramps
Diamond Plate Drive-Over Fenders
Electric Brake Axles (2)
Slipper Spring Suspension
Silver Wheels
Epoxy Primer

Polyurethane Paint Finish
Pressure-Treated Pine Decking (Oak on 8 Ton)
Spare Tire Mount
D-Ring Tie-Downs (2)
Stake Pockets (14)
Rub Rail
Aluminum Toolbox
Banjo Eye Tie-Downs (2)
Sealed Wiring Harness
LED Lights – Rubber Mounted
Three Year Warranty

Specifications subject to change without notice.





SPECIFICATIONS PAGE

FULL WIDTH EQUIPMENT HAULER

	10K	14K	14K	14K	16K	16K	16K
Model #	P5EC182CFW	P7EC182CFW	P7EC202CFW	P7EC222CFW	P8EC182CFW	P8EC202CFW	P8EC222CFW
GVWR (lb.)	11000	15400	15400	15400	17600	17600	17600
GAWR (lb. / Axle)	5200	7000	7000	7000	8000	8000	8000
Curb Weight	2900	3160	3350	3550	4060	4210	4360
Payload	8100	12240	12050	11850	13540	13390	13240
Frame	5" Channel	6" Channel @ 8.2 lbs.			6" Channel @ 10.5 lbs.		
Crossmembers	10 Guage, Formed	3" Channel					
Tongue	5" Channel @ 6.7lbs	6" Channel @ 8.2 lbs.			6" Channel @ 10.5 lbs.		
Coupler	Adjustable 2-5/16" Ball Coupler or Pintle Ring						
Jack	7K Bolt-on Drop Leg Jack	12K Bolt-on Drop Leg Jack					
Fenders	Diamond Plate Drive Over Fenders						
Axles	5,200 lb, Greased	7,000 lb, Greased			8,000 lb, Oil Bath		
Suspension	Slipper Spring Suspension						
Tires	225/75R15 LRD	235/80R16 LRE			215/75R17.5 LRH		
Wheels	15"	16"			17.5"		
Decking	Pressure-Treated Decking				Oak Decking		
Lights	LED Lights - Rubber Mounted						
Electric Plug	7-Way SAE Plug						
Finish	PPG Industrial Polyurethane Paint						
Overall Length / Flat	284"		308"	332"	284"	308"	332"
Deck Width	81"						
Deck Height	22.5"	25"			26"		
Coupler Height	16.5" - 21"	17" - 21.5"			18" - 22.5"		
Ramps	5' Steel Fabricated Ramps	5' Quick Release Angle Ramps					



Specifications subject to change without notice.

