



SPECIFICATIONS PAGE

LOW PROFILE DUMP TRAILER



LOW PROFILE DUMP STANDARD FEATURES

Tubular Main Frame
Adjustable 2-5/16" Ball Coupler or Pintle Ring
Safety Chains
7-Way SAE Plug
Breakaway Switch
Charge Wire with Circuit Breaker
7K Bolt-On Drop Leg Jack
Slide-Out Ladder Ramps (6')
Triple-Acting Tailgate w/ Chains
Diamond Plate Fenders
EZ Lube Axles
Electric Brake Axles (2)
Nev-R-Adjust Brakes
Slipper Spring Suspension
Silver Wheels

Epoxy Primer
Polyurethane Paint Finish
10-Gauge Floor
12-Gauge Sides
Spare Tire Mount
D-Ring Tie-Downs - 1/2" (4)
2" x 4" Full Height Stake Pockets
Tie Down Rail
Sealed Wiring Harness
LED Lights – Rubber Mounted
Aluminum Lockable Pump Box
Remote Control with 20' Cord
12V Deep-Cycle Battery
110V Battery Charger
Three Year Warranty

Specifications subject to change without notice.





SPECIFICATIONS PAGE

LOW PROFILE DUMP TRAILER

| | 72.5" x 10' | 72.5" x 12' |
|--------------------|--|----------------|
| Model # | P5CAM610LPD | P5CAM612LPD |
| GVWR (lb.) | 11000 | 11000 |
| GAWR (lb. / Axle) | 5200 | 5200 |
| Curb Weight | 2600 | 2820 |
| Payload | 8400 | 8180 |
| Frame | 6" x 2" x 3/16" rec tube | |
| Crossmembers | 3" Channel | |
| Tongue | 5" Channel | |
| Coupler | Adjustable 2-5/16" Ball Coupler or Pintle Ring | |
| Jack | 7K Bolt-On Drop Leg Jack | |
| Fenders | Diamond Plate | |
| Axles | 5,200 lb, Greased | |
| Suspension | Equalized Slipper Spring Suspension | |
| Tires | 225/75R15 LRD | |
| Wheels | 15" | |
| Volume Capacity | 3.9 cu yd. | 4.6 cu yd. |
| Lights | LED Lights - Rubber Mounted | |
| Electric Plug | 7-Way SAE Plug | |
| Finish | PPG Industrial Polyurethane Paint | |
| Overall Length | 164" | 188" |
| Bed Width Inside | 72.5" | |
| Bed Length Inside | 120" | 144" |
| Side Wall Height | 20.5" | |
| Deck Height | 28" | |
| Coupler Height | 17.5" - 24.25" | |
| Gate | Triple-Acting Tailgate w/Chains | |
| Hydraulic Cylinder | One 3.5" x 36" | One Telescopic |
| Hydraulic Pump | 12V Single Acting | |
| Battery | 12V Deep-Cycle Battery | |
| Dump Angle | 48° | 46° |

Specifications subject to change without notice.

