

LOW PROFILE HEAVY DUTY DUMP TRAILER



LOW PROFILE HD DUMP STANDARD FEATURES

- Tubular Main Frame
- 102" Width
- Adjustable 2-5/16" Ball Coupler or Pintle Ring
- Safety Chains
- 7-Way SAE Plug
- Breakaway Switch
- Charge Wire with Circuit Breaker
- 7K Bolt-On Drop Leg Jack (12K on 7 & 8 Ton)
- Slide-Out Ladder Ramps (6')
- Triple-Acting Tailgate w/ Chains
- Diamond Plate Fenders
- EZ Lube Axles
- Electric Brake Axles (2)
- Nev-R-Adjust Brakes
- Slipper Spring Suspension
- Silver Wheels
- Epoxy Primer

- Polyurethane Paint Finish
- 10-Gauge Floor
- 12-Gauge Sides
- Spare Tire Mount
- D-Ring Tie-Downs - 1/2" (4)
- 2" x 4" Full Height Stake Pockets
- Tie Down Rail
- Storage Tray
- Rear Stabilizer Legs
- Sealed Wiring Harness
- LED Lights – Rubber Mounted
- Aluminum Lockable Pump Box
- Remote Control with 20' Cord
- 12V Deep-Cycle Battery
- 110V Battery Charger
- Three Year Warranty

Specifications subject to change without notice.



SPECIFICATIONS PAGE

LOW PROFILE HEAVY DUTY DUMP TRAILER

	6'x12'	6'x14'	6'x14'	6'x16'	6'x14'	6'x16'
Model #	P6CAM612LPHD	P6CAM614LPHD	P7CAM614LPHD	P7CAM616LPHD	P8CAM614LPHD	P8CAM616LPHD
GVWR (lb.)	13200	13200	15400	15400	17600	17600
GAWR (lb. / Axle)	6000	6000	7000	7000	8000	8000
Curb Weight	3740	4040	4080	4340	5470	5730
Payload	9460	9160	11320	11060	12130	11870
Frame	6" x 3" x 3/16" Rec. Tube			6" x 3" x 1/4" Rec. Tube	6" x 3" x 3/16" Rec. Tube	6" x 3" x 1/4" Rec. Tube
Crossmembers	3" Channel					
Tongue	5" Channel					
Coupler	Adjustable 2-5/16" Ball Coupler or Pintle Ring					
Jack	7K Bolt-On Drop Leg Jack			12K Bolt-On Drop Leg Jack		
Fenders	Diamond Plate					
Axles	6,000 lb, Greased		7,000 lb Greased		8,000 lb, Oil Bath	
Suspension	Slipper Spring Suspension					
Tires	235/80R16 LRE				215/75R17.5 LRH	
Wheels	16"				17.5"	
Volume Capacity	5.16 cu yd	6.02 cu yd	6.02 cu yd	6.87 cu yd	6.02 cu yd	6.87 cu yd
Lights	LED Lights - Rubber Mounted					
Electric Plug	7-Way SAE Plug					
Finish	PPG Industrial Polyurethane Paint					
Overall Length	188"	212"		236"	212"	236"
Bed Width Inside	81.5"					
Bed Length Inside	144"	168"		192"	168"	192"
Side Wall Height	20.5"					
Deck Height	29"	29"	29"	29"	30"	30"
Coupler Height	18.5" - 23"				19.5" - 24"	
Gate	Triple-Acting Tailgate w/Chains					
Hydraulic Cylinders	Two Telescopic Cylinders					
Hydraulic Pump	12V Single Acting					
Battery	12V Deep Cycle Battery					
Dump Angle	46°	45°		43°	45°	43°

Specifications subject to change without notice.

