



SPECIFICATIONS PAGE

SPLIT TILT DECKOVER TRAILER



SPLIT TILT DECKOVER STANDARD FEATURES

- Steel Plated Tongue
- Adjustable 2-5/16" Ball Coupler or Pintle Ring
- Safety Chains
- 7-Way SAE Plug
- Zip Breakaway System
- 12K Bolt-On Drop Leg Jack
- Knife Edge Approach
- Rear Impact Guard
- EZ Lube Axles
- Electric Brakes Axles (2)
- Nev-R-Adjust Brakes
- Slipper Spring Suspension
- Silver Wheels

- Epoxy Primer
- Polyurethane Paint Finish
- Pressure-Treated Pine Decking (Oak on 8 Ton)
- Spare Tire Mount
- D-Ring Tie-Downs - 5/8" (8)
- Stake Pockets and Rub Rail
- Aluminum Toolbox
- Mud Flaps
- Sealed Wiring Harness
- LED Lights – Rubber Mounted
- Power Up / Power Down
- Dual Hydraulic Cylinders
- Three Year Warranty

Specifications subject to change without notice.





SPECIFICATIONS PAGE

SPLIT TILT DECKOVER TRAILER

	14K	16K
Model #	P7CAM824DOSTT	P8CAM824DOSTT
GVWR (lb.)	15400	17600
GAWR (lb. / Axle)	7000	8000
Curb Weight	4580	5130
Payload	10820	12470
Main Frame	8" I-Beam @ 10 lbs.	8" I-Beam @ 13 lbs.
Crossmembers	3" Channel	
Side Rail	5" Channel @ 6.7 lb	
Tongue	8" I-Beam @ 10 lbs.	8" I-Beam @ 13 lbs.
Coupler	Adjustable 2-5/16" Ball Coupler or Pintle Ring	
Jack	12K Bolt-On Drop Leg Jack	
Axles	7,000 lb, Greased	8,000 lb, Oil Bath
Suspension	Slipper Spring Suspension	
Tires	235/80R16 LRE	215/75R17.5 LRH
Wheels	16" Spoke	17.5" Mod
Decking	Pressure-Treated Pine Decking	Oak Decking
Lights	LED Lights - Rubber Mounted	
Electric Plug	7-Way SAE Plug	
Finish	PPG Industrial Polyurethane Paint	
Overall Length	348"	
Deck Height	35"	36"
Coupler Height	20.5" - 29.5"	21.5" - 30.5"
Approach Plate	Knife Edge Approach	
Load Angle	16°	17°

Specifications subject to change without notice.

