



SPECIFICATIONS PAGE

EXTRA WIDE SPLIT DECK TILT TRAILER



EXTRA WIDE SPLIT DECK TILT STANDARD FEATURES

Adjustable 2-5/16" Ball Coupler or Pintle Ring
Safety Chains
7-Way SAE Plug
Zip Breakaway System
7K Bolt-On Drop Leg Jack (12K on 7 & 8 Ton)
Removable Diamond Plate Fenders
EZ Lube Axles 4" Drop
Torflex Axles
Electric Brake Axles (2)
Nev-R-Adjust Brakes
Silver Wheels
Epoxy Primer

Polyurethane Paint Finish
Pressure-Treated Pine Decking (Oak on 8 Ton)
Spare Tire Mount
(8) D-Ring Tie Downs – 5/8" (4 Stat., 4 Tilt)
Pallet Fork Carrier (N/A w/Gooseneck)
Aluminum Toolbox
Banjo Eye Tie-Downs (2)
Sealed Wiring Harness
LED Lights – Rubber Mounted
Adjustable Hydraulic Cushion Cylinder
Three Year Warranty

Specifications subject to change without notice.





SPECIFICATIONS PAGE

EXTRA WIDE SPLIT DECK TILT TRAILER

	12K	14K	16K
Model #	P6CAM154STTXW	P7CAM154STTXW	P8CAM154STTXW
GVWR (lb.)	13200	15400	17600
GAWR (lb. / Axle)	6000	7000	8000
Curb Weight	3280	3500	4230
Payload	9920	11900	13370
Frame	6"x4"x5/16" Angle	6"x4"x3/8" Angle	6"x4"x1/2" Angle
Crossmembers	3" Channel		
Tongue	6" Channel @ 8.2 lbs.	6" Channel @ 10.5 lbs.	
Coupler	Adjustable 2-5/16" Ball Coupler or Pintle Ring		
Jack	7K Bolt-On Drop Leg Jack	12K Bolt-On Drop Leg Jack	
Fenders	Removable Diamond Plate Fenders		
Axles	6,000 lb, Greased	7,000 lb, Greased	8,000 lb, Oil Bath
Suspension	Torflex Axles		
Tires	235/80R16 LRE		215/75R17.5 LRH
Wheels	16" Spoke		17.5" Mod
Decking	Pressure-Treated Pine Decking		Oak Decking
Lights	LED Lights - Rubber Mounted		
Electric Plug	7-Way SAE Plug		
Finish	PPG Industrial Polyurethane Paint		
Overall Length	282"		
Between Fenders	83"		
Deck Height	22"		23"
Coupler Height	20.5" - 25"		21.5" - 26"
Load Angle	14°		

Specifications subject to change without notice.

