

	18' 22K	20' 22K	22' 22K
Model #	PFTB8218-BP-220	PFTB8220-BP-220	PFTB8222-BP-220
GVWR (lb.)	22000	22000	22000
GAWR (lb. / Axle)	10000	10000	10000
Curb Weight	4840	5100	5360
Payload	17160	16900	16640
Frame	W8 x 15 Beam		
Crossmembers	3" Channel		
Tongue	W8 x 15 Beam		
Coupler	Adjustable Nose Plate Pintle Ring		
Jack	12K 2-Speed Set-Back Jack		
Fenders	Diamond Plate		
Axles	10,000 lb Oil Bath		
Suspension	Torsion Suspension		
Tires	215/75R17.5 LRH		
Wheels	17.5", 8 on 6.5		
Decking	Pressure-Treated Pine		
Lights	LED Lights - Rubber Mounted		
Electric Plug	7-Way SAE Plug		
Finish	PPG Industrial Polyurethane Paint		
Total Length/Flat Deck/Usable	277"/222"/217"	301"/246"/241"	325"/270"/265"
Between Fenders	82"		
Deck Height	25"		
Coupler Height	21.25" - 31.25"		
Load Angle	14°		

ADDITIONAL FEATURES

- HD Steel Bulkhead
- Zip Breakaway System
- 12K 2-Speed Set-Back Jack
- Knife Edge Approach
- Spare Tire Mount
- D-Ring Tie Downs - 3/4" (4)
- Full-Size Integrated Lockable Steel Toolbox
- LED Toolbox Light
- Slip-Resistant Deck Access Step
- Banjo Eye Tie-Downs (2)
- Sealed Wiring Harness
- Adjustable Hydraulic Cushion Cylinder
- Three Year Warranty

