

	82" x 12' 13.2K	82" x 14' 13.2K	82" x 14' 15.4K	82" x 16' 15.4K	82" x 14' 17.6K	82" x 16' 17.6K
Model #	PTLB8212-BP-132	PTLB8214-BP-132	PTLB8214-BP-154	PTLB8216-BP-154	PTLB8214-BP-176	PTLB8216-BP-176
GVWR (lb.)	13200	13200	15400	15400	17600	17600
GAWR (lb. / Axle)	6000	6000	7000	7000	8000	8000
Curb Weight	4240	4500	4540	4800	5040	5300
Payload	8960	8700	10860	10600	12560	12300
Frame	6" x 3" x 3/16" Rec. Tube			6" x 3" x 1/4" Rec. Tube	6" x 3" x 3/16" Rec. Tube	6" x 3" x 1/4" Rec. Tube
Crossmembers	3" Channel					
Tongue	5" Channel					
Sides	24"					
Coupler	Adjustable 2-5/16" Ball Coupler					
Jack	12K Bolt-On Drop Leg 2-Speed Jack					
Fenders	Diamond Plate					
Axles	6,000 lb. Greased		7,000 lb Greased		8,000 lb. Oil Bath	
Suspension	Slipper Spring Suspension					
Tires	235/80R16 LRE				215/75R17.5 LRH	
Wheels	16", 8 on 6.5, Radial				17.5", 8 on 6.5, Radial	
Decking	7 gauge, Smooth Steel					
Volume Capacity	6.07 cu yd	7.09 cu yd	7.09 cu yd	8.10 cu yd	7.09 cu yd	8.10 cu yd
Lights	LED Lights - Rubber Mounted					
Electric Plug	7-Way SAE Plug					
Finish	PPG Industrial Polyurethane Paint					
Overall Length	188"	212"		236"	212"	236"
Bed Width Inside	81.5"					
Bed Length Inside	144"	168"		192"	168"	192"
Side Wall Height	20.5"					
Deck Height	29"	29"	29"	29"	30"	30"
Coupler Height	18.5" - 23"				19.5" - 24"	
Gate	Triple-Acting Tailgate w/Chains					
Hydraulic Cylinders	Two Telescopic Cylinders-Power-Up, Gravity-Down					
Hydraulic Pump	12V Single Acting					
Battery	12V Deep Cycle Battery Group 31					
Dump Angle	46°	45°		43°	45°	43°

ADDITIONAL FEATURES

- Safety Chains
- Zip Breakaway System
- Rear Stabilizer Legs
- 7-Gauge Floor
- Spare Tire Mount
- Stake Pockets and Rub Rail
- Integrated Tarp Shroud
- Mesh Tarp Installed
- Steps (4)
- Storage Tray
- Sealed Wiring Harness
- Steel Lockable Pump Box
- Remote Control with 20' Cord
- 110V Battery Charger
- Three Year Warranty

