



DECKOVER TRAILERS

HEAVY DUTY - GOOSNECK

| | 20' + 5' 22.5K | 20' + 5' 25.9K | 25' + 5' 22.5K | 25' + 5' 25.9K |
|--------------------------|-------------------------------------------------------|-------------------|-------------------------------------------------------|-------------------|
| Model # | PHD0102205-GN-225 | PHD0102205-GN-259 | PHD0102255-GN-225 | PHD0102255-GN-259 |
| GVWR (lb.) | 22500 | 25900 | 22500 | 25900 |
| GAWR (lb. / Axle) | 10000 | 12000 | 10000 | 12000 |
| Curb Weight | 5990 | 6265 | 7375 | 7575 |
| Payload | 16510 | 19635 | 15125 | 18325 |
| Main Frame | 12" I-Beam @ 14 lb | | 12" I-Beam @ 19 lb | |
| Crossmembers | 3" Channel | | 3" Channel | |
| Side Rail | 6" Channel @ 8.2 lb | | 6" Channel @ 8.2 lb | |
| Tongue | 12" I-Beam @ 14 lb | | 12" I-Beam @ 19 lb | |
| Beavertail | 5' Self-Cleaning Beavertail | | 5' Self-Cleaning Beavertail | |
| Coupler | Adjustable Pintle Ring | | Adjustable Pintle Ring | |
| Jack | 12K Bolt-On Drop Leg Jack | | 12K Bolt-On Drop Leg Jack | |
| Axles | Oil Bath | | Oil Bath | |
| Suspension | Slipper Spring Suspension | | Slipper Spring Suspension | |
| Tires | 235/80R16 LRE Dual | | 235/80R16 LRE Dual | |
| Wheels | 16" Dual | | 16" Dual | |
| Decking | Pressure Treated Pine Decking | | Pressure Treated Pine Decking | |
| Lights | LED Lights - Rubber Mounted | | LED Lights - Rubber Mounted | |
| Electric Plug | 7-Way SAE Plug | | 7-Way SAE Plug | |
| Finish | PPG Industrial Polyurethane Paint | | PPG Industrial Polyurethane Paint | |
| Overall Length | 426" | | 450" | |
| Deck Height | 32" | | 32" | |
| Coupler Height | 31" - 39.75" | | 31" - 39.75" | |
| Ramps | HD Fabricated Fold Flat w/Double Hinged Spring Assist | | HD Fabricated Fold Flat w/Double Hinged Spring Assist | |

Additional configurations available. Refer to the dealer portal or contact your sales representative for more information.

ADDITIONAL FEATURES

- Full Pierced Beam Construction
- HD Steel Bulkhead
- HD I-Beam Gooseneck
- Zip Breakaway System
- Diamond Plate Deck Over Wheels
- D-Ring Tie Downs - 5/8" (6)
- Stake Pockets and Rub Rail
- Side Steps
- Sealed Wiring Harness
- Three Year Warranty



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.