

## **DECKOVER TRAILERS**

## **STANDARD DUTY**

		8.5 x 20	8.5 x 22	8.5 x 24
Model #	Bumper Pull	PSD010220-BP-154	PSD010222-BP-154	PSD010224-BP-154
	Gooseneck	PSD010220-GN-154	PSD010222-GN-154	PSD010224-GN-154
GVWR (lbs)		15400	15400	15400
GAWR (lbs/axle)		7000	7000	7000
Curb Weight	Bumper Pull	2685	3070	3457
	Gooseneck	3490	3870	4257
Payload	<b>Bumper Pull</b>	12715	12330	11943
	Gooseneck	11910	11530	11143
Main Frame		W10 x 12#/ft., I-Beam		
Side Rails		5" C-Channel		
Cross Members		3" C-Channel (16" On-Center)		
Coupler	Bumper Pull	Adjustable 2-5/16" Ball Coupler		
	Gooseneck	Adjustable 2-5/16" Gooseneck Coupler		
Jack	Bumper Pull	Setback HD 12K Drop Leg Jack		
	Gooseneck	Dual Setback HD 12K Drop Leg Jacks with Toolbox (Between Uprights), Tool Tray and Winch Receiver Tube (In Neck)		
Axles		Easy Lube Hubs with Brakes		
Suspension		Slipper Spring		
Tires		235/80R16 LRE		
Wheels		16", 8 on 6.5, Radial		
Decking		2 x 8 Pressure Treated Pine		
Lights		All LED Lights		
Electric Plug		7-Way RV-Style Molded Plug		
Finish		PPG Industrial Polyurethane Paint		
Overall Length	<b>Bumper Pull</b>	290"	314"	338"
	Gooseneck	348"	372"	396
Deck Height		36"	36"	36"
Coupler Height	Bumper Pull	Adjustable 21"-29"		
	Gooseneck	Adjustable 31" - 39-3/4"		
Ramps		8' Slide-In Fabricated Ramps		

Additional configurations available. Refer to the dealer portal or contact your sales representative for more information.

## **ADDITIONAL FEATURES**

HD Steel Bulkhead Safety Chains Zip Breakaway System Spare Tire Mount D-Ring Tie Downs (6) Stake Pockets and Rub Rail Sealed Wiring Harness Three Year Warranty









Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.